

Personal flotation devices (buoyancy aids and life jackets) have different levels of buoyancy. These levels of buoyancy should be considered and influence your choice, when selecting a personal flotation device. There are four main buoyancy levels; 50, 100, 150 and 275. In general terms, Level 50 is a buoyancy aid designed for when help is close at hand, whereas Level 150 is a general purpose lifejacket used for offshore cruising and motor boating.

To determine these levels of buoyancy under test conditions, the test subjects (real people) are dressed in bathing costumes. This requirement provides good consistency and repeatability for testing, but needs to be taken into account in your selection, as foul weather clothing or babies nappies are likely to adversely affect the performance level. This is particularly true with Level 100 and 150, when turning a person over so their head is clear of the water. A garment that is the incorrect size for the wearer will adversely affect the performance level.

Level 50

Example



Label



This level is intended for use by those who are competent swimmers and who are near to bank, shore, or who have help and a means of rescue close at hand. These garments have minimal bulk, but they are of limited use in disturbed water, and cannot be expected to keep the user safe for a long period of time. They do not have sufficient buoyancy to protect people who are unable to help themselves. They require active participation by the user. Standards applicable to this level; EN 393 or ISO 12402 – 5.

Level 100

Example



Label



This level is intended for those who may have to wait for rescue, but are likely to do so in sheltered water. The device should not be used in rough conditions. Standards applicable to this level; EN 395 or ISO 12402 – 4.

Level 150

Example



This level is intended for general offshore and rough weather use where a high standard of performance is required. It will turn an unconscious person into a safe position and requires no subsequent action by the user to maintain this position. Standards applicable to this level; EN 396 or ISO 12402 – 3.

Label



Level 275

Example



This level is intended primarily for offshore use and by people who are carrying significant weights and thus require additional buoyancy. It is also of value to those who are wearing clothing which traps air and which may adversely affect the self-righting capacity of the lifejacket. It is designed to ensure that the user is floating in the correct position with their mouth and nose clear of the surface. Standards applicable to this level; EN 399 or ISO 12402 – 2.

Label



Lifejacket and buoyancy aid images reproduced with the kind permission of Baltic Safety Products.